





Large Capacity Battery System Designed For PV Residential Application.

Battery Series

M48112-P



-  Plug & Play
-  Modular
-  Safety
-  Long Lifespan

Physical

Model	M48112-P
Battery Type	LiFePO ₄ (LFP)
Battery Manufacturer	EVE <small>ENERGY VERY ENDURE</small>
System Weight	63 kg
Dimension (W x D x H)	482 x 580 x 158 mm
Protection Level	IP20

Electrical

Installed Capacity	5.4 kWh
Usable Capacity	4.8 kWh
DOD	90%
Nominal Voltage	48 V
Operation Voltage Range	46 - 54 V
Internal Resistance	≤30 mΩ
Cycle Life	≥6000

Warranty

Product Warranty	5 Years
Performance Warranty	10 Years

BMS

Power Consumption	<2 W (Work) <100 mW (Sleep)
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature.
SOC	Intelligent algorithm
Communication	CAN and RS-485 compatible

System Configuration

Module Parallel	1-6 Parallels
Capacity Range	5.4/10.8/16.1/21.5/26.9/32.3 kWh

Operation

Max. Charge Current	56 A (0.5C)
Max. Discharge Current	56 A (0.5C)
Operating Temperature Range	-10°C ~ 50°C
Transport Or Storage Temperature Range	-20°C ~ 45°C
Humidity	15% ~ 85% (No Condensing)

Cabinet

Dimension (W x D x H)	600 x 600 x 990/1390 mm
Max. Modules	4/6
Color	Black
Protection Level	IP20

* When the temperature is below 0°C, batteries are not allowed to be charged, and they will derate power output when it is above 40°C.



Headquarter:

+86 (0)513 806 068 91
 info@alpha-ess.com
 www.alpha-ess.com
 JiuHua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Germany:

+49 (0)6103 / 459 160-1
 europe@alpha-ess.de
 www.alpha-ess.de
 Paul-Ehrlich-Straße 1a, 63225 Langen, Hessen

Italy:

+39 335 5627462
 info@alpha-ess.it
 www.alpha-ess.it
 Via Loda, 17-41013 Castelfranco Emilia(MO) C./F./P.IVA 03767340361



Official Website



WeChat